

DECLARATION OF PERFORMANCE

DOP N°047-2025-01

1. Unique identification code of the product-type: **82-004**

Commercial name : **SUPER BOOST'R, ULTRA BOOST'R, BOOST'R MAX**

2. Intended use/es:

Underlay for discontinuous roofing.
Underlay for walls.

3. Manufacturer :

ACTIS S.A.
30, avenue de Catalogne
F-11300 LIMOUX
www.actis-isolation.com

4. Authorised representative: **Not applicable**

5. System/s of AVCP: **System 3**

6. Harmonised standard:

EN 13859-1 : 2010
EN 13859-2 : 2010

Notified body/ies:

IBP, notified body no. 1004

7. Declared performance/s:

DECLARATION OF PERFORMANCE

DOP N°047-2025-01

Essential characteristics		Performances	Harmonised technical specifications
Fire resistance		NPD	EN 13859-1 : 2010 EN 13859-2 : 2010
Water tightness (before and after artificial ageing)		W1	
Tensile strength properties (before ageing)	Maximum tensile strength - longitudinal direction - transversal direction	> 300 N/50mm > 150 N/50mm	
	Elongation - longitudinal direction - transversal direction	> 20 % > 5 %	
Tensile strength properties (after ageing)	Maximum tensile strength - longitudinal direction - transversal direction	> 100 N/50mm > 100 N/50mm	
	Elongation - longitudinal direction - transversal direction	< 15 % < 5 %	
Nail tear resistance - longitudinal direction - transversal direction		> 150 N > 150 N	
Flexibility at low temperature (pliability)		- 30°C	
Dangerous substances (emissions in indoor air)		A+	
Water vapour transmission external membrane		Sd < 1 m	EN 13859-2 : 2010

8. Appropriate Technical Documentation and/or Specific Technical Documentation : Not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Laurent THIERRY
Chairman / Managing Director

At Limoux, on 03/11/2025

